

# STOCKCLIENT

## Selected Endpoint Documentation

StockClientWebAPI

Base URL: <https://stockclientwebapi.azurewebsites.net>

## Get Recent Delivery Notes

GET /StockDeliveryNotes/GetByCompanyAndCenter

Authentication: No Authentication

Returns non-deleted delivery notes ordered by creation date. Default range is the last 3 months. Parameters: CompanyGuid (GUID, required), Version (integer, required). Response fields: Id, Code, IdCenter, DeliveryDate, CreateDate, transport information, IdCompany, IdState, Deleted. Errors: 400 Invalid GUID, 500 Internal Error.

Example:

GET /StockDeliveryNotes/GetByCompanyAndCenter?CompanyGuid=11111111-1111-1111-1111-111111111111&Version=1

## Create Delivery Note

POST /StockDeliveryNotes/StockDeliveryNoteCreate

Authentication: No Authentication

Creates a delivery note and updates inventory. Query parameters: CompanyGuid (GUID, required), Version (integer, required), CenterCode (string, required). Required fields: code, lines, and productCode in each line. Optional: lotNo, serialNumber, expiry. Response: { success: true, deliveryNoteId: 123 }. Errors: 400 Validation Error, 500 Internal Error.

Example:

```
{
  "deliveryDate":"2026-09-17T00:00:00",
  "code":"ALB-000123",
  "lines":[{
    "productCode":"PRODUCTO-001",
    "qty":5,
    "lotNo":"LOTE-01",
    "serialNumber":"SERIE-01",
    "expiry":"2027-12-31T00:00:00"
  }]
}
```

## Get Pending Movements

GET /StockMovProductsExport/PendingMovements

Authentication: HTTP Basic Required

Parameters: clientCode (GUID, required), version (integer, required). Returns pending ERP movements including id, idProduct, productCode, qty, lotNo, serialNumber, expiryDate, idStore, centerCode, clientCode, createDate and erpImport. Errors: 400 Invalid GUID, 401 Unauthorized, 500 Internal Error.

Example:

GET /StockMovProductsExport/PendingMovements?clientCode=11111111-1111-1111-1111-111111111111&version=1

## Mark Imported Movements

POST /StockMovProductsExport/MarkImportedMovements

Authentication: HTTP Basic Required

Query parameter: clientCode (GUID, required). Body parameter: ids (integer array, required). Response: { "updated": 3, "requested": 3 }. Errors: 400 Invalid Request, 401 Unauthorized, 500 Internal Error.

Example:

{ "ids": [101, 102, 103] }

## Get Orders Pending Supplier Code

GET /StockOrder/PendingSupplierOrders

Authentication: No Authentication

Parameters: CompanyGuid (GUID, required), Version (integer, required). Returns orderGuid, centerName, clientName, clientCode, createDate, code and patientCode. Returns orders from the last three months with empty SupplierOrderCode.

## Get Order Details

GET /StockOrder/OrderDetails

Authentication: No Authentication

Parameter: orderGuid (GUID, required). Response fields: orderGuid, code, patientCode, centerCode, clientCode, companyCode, deliveryDate, deliveryData, deliveryService and lines. Each line contains idProduct, productCode, productDescription, qty and percentDiscount. Errors: 404 Not Found, 500 Internal Error.

## Update Supplier Order Code

POST /StockOrder/SupplierOrderCode

Authentication: No Authentication

Query parameter: orderGuid (GUID, required). Body parameter: supplierOrderCode (string, required, non-empty). Response: success, orderGuid, supplierOrderCode. Errors: 400 Validation Error, 404 Not Found, 500 Internal Error.

Example:

```
{  
  "supplierOrderCode":"PROV-2026-000123"  
}
```

Response:

```
{  
  "success": true,  
  "orderGuid":"11111111-1111-1111-1111-111111111111",  
  "supplierOrderCode":"PROV-2026-000123"  
}
```